

Tesi Join is the new addition to the Tesi Collection with winding, attractive lines. Interlacing pipes make this heating element the star of any room.



Tesi Join, Vertical, 10 elements, Height 2002 mm, Length 474 mm, Pearl White

Construction features

- sheet steel tubes with diameter 25 mm;
- moulded sheet steel manifolds;
- element length 45 mm;
- manifold top and bottom end threads 1/2" G right;
- maximum allowed working pressure 8 bar;
- maximum allowed working temperature 95°C.

Standard equipment

- 1 hydraulic connection kit (valve and lockshield valve) in a finish coordinated with the radiator, equipped with copper fittings (12, 14 mm diameter) and multilayer pipes (14 x 2 thick and 16 x 2 thick)
- 1 kit for fixing to the wall in a finish coordinated with the radiator
- chromium-plated hidden vent valve
- one 1/2" end plug complete with chrome-plated cover
- 1 kit of satin-finished pipe covers

N.B. The valves provided are a valve and lockshield valve in a angle version or angle valve assembly with pitch 50 mm for versions with a 50 mm connection.

Plus



Technical data

Model	Deph (mm)	Height (mm)	Width (mm)	Conn. C. (mm)	Weigth (kg)	Capacity (lt)	COM_PRODUCTS_TABLE_DATA_BTU	$\Delta t=50^{\circ}\text{C}$ (kcal/h)	$\Delta t=50^{\circ}\text{C}$ (Watt)	$\Delta t=40^{\circ}\text{C}$ (Watt)	$\Delta t=30^{\circ}\text{C}$ (Watt)	$\Delta t=20^{\circ}\text{C}$ (Watt)	Exponent
1800 08 el.	65,0	1802	391	1735	19,30	13,10	2.917,6	855,2	994,4	739,2	504,0	294,4	1,329
1800 10 el.	65,0	1802	481	1735	24,10	16,40	3.647,0	1.069,0	1.243,0	924,0	630,0	368,0	1,329
1800 12 el.	65,0	1802	571	1735	28,90	19,70	4.376,4	1.282,8	1.491,6	1.108,8	756,0	441,6	1,329
2000 08 el.	65,0	2002	391	1935	21,40	14,40	3.263,2	956,0	1.112,0	828,8	567,2	332,0	1,319
2000 10 el.	65,0	2002	481	1935	26,70	18,00	4.079,0	1.195,0	1.390,0	1.036,0	709,0	415,0	1,319
2000 12 el.	65,0	2002	571	1935	32,00	21,60	4.894,8	1.434,0	1.668,0	1.243,2	850,8	498,0	1,319

Thanks to the high performance of Irsap Tesi Join radiators, the ideal Δt for low temperature projects is Δt at 30°C .


For Δt different from 50°C use the formula: $Q=Q_n (\Delta t / 50)^n$

Standard equipment

- 1 hydraulic connection kit (valve and lockshield valve) in a finish coordinated with the radiator, equipped with copper fittings (12, 14 mm diameter) and multilayer pipes (14 x 2 thick and 16 x 2 thick)
- 1 kit for fixing to the wall in a finish coordinated with the radiator
- chromium-plated hidden vent valve
- one 1/2" end plug complete with chrome-plated cover
- 1 kit of satin-finished pipe covers N.B. The valves provided are a valve and lockshield valve in a angle version or angle valve assembly with pitch 50 mm for versions with a 50 mm connection.


Colors and Finishes

STANDARD




Bianco Standard
Cod. 01


CLASSIC



Bianco Edelweiss
Opaco
Cod. 34



Bianco Whisper
Peach
Cod. 36




Avorio - RAL 1013
Cod. 02




Jasmin Opaco
Cod. 35




Beige Naturale
Cod. 38




Beige Cream
Cod. 26



Giallo - RAL 1021
Cod. 04




Giallo Melone - RAL
1028
Cod. E7



Arancio - RAL 2004
Cod. 17



Marrone Ruggine -
RAL 8004
Cod. E1



Marrone - RAL 8017
Cod. 09



Vinaccia - RAL 3005
Cod. H9




Amaranto - RAL 3003
Cod. 06




Rosso - RAL 3000
Cod. 05



Rosso Fragola - RAL
3018
Cod. Y3



Rosa - RAL 3015
Cod. R2



Lilla Bluastro - RAL
4005
Cod. R3



Porpora Traffico -
RAL 4006
Cod. R6




Verde Bosco - RAL
6005
Cod. 19




Verde Erba - RAL
6018
Cod. N3




Verde Salvia - RAL
6021
Cod. E6




Verde Greenwich
Cod. 28




Blu Pastello - RAL
5024
Cod. G7




Blu Colomba - RAL
5014
Cod. G9




Blu Hewi
Cod. 11



Grigio Manhattan
Cod. 03










Nero - RAL 9005
Cod. 10





Deep Blue
Cod. 2F

SPECIAL

							
Bianco Perla Cod. 16	Quartz 1 Cod. 1C	Sablé Cod. Y4	Quartz 2 Cod. 2C	Sunstone Cod. 2D	Petra Cod. 3D	Bruno Tabacco Cod. 1B	Flame Red Cod. 7D
							
Purple Blue Cod. 1D	Azurite Cod. 6D	Azurite 3 Cod. 6C	Grigio Medio Cod. 4D	Grigio Titanio Metallizzato - RAL 9023 Cod. L3	Grigio Silver Cod. 5D	Grigio Perla Cod. L6	Grigio Alluminio - RAL 9006 Cod. B4
							
Nero Grafite Cod. 18	Grigio Quarzo Cod. 31	Nero Satinato Cod. 30	Luxury White Cod. J7	Bianco Opaco Cod. J8	Nero Opaco Cod. K1	Bronzo Cod. J9	Grigio Martellato Cod. 32
							
Luxury Black Cod. J3	Rame Martellato Cod. J4						

SURFACES

				
Trattamento Loft Cod. TR	Taftah Argento Cod. K4	Taftah Platino Cod. K3	Taftah Oro Cod. K2	Grey Shadow Cod. X6

The Colors used in this folder are not considered binding. The different technological painting processes and the materials used for the realization can not have a perfect color match with the delivered product. Irsap company reserves the right to introduce at any time whatever modifications necessary to the improvement of the product.