

FORM ONDULATO

The Form F2H radiator is standard produced in the FORM ONDULATO model with just two curves: curvature is more accentuated

in the upper part and less pronounced in the lower part. The result is a "wavy" object of remarkably contained depth (from 9 to 12

cm) with an extremely pleasing appearance. Also available made-to-measure according to the Form F2H and F2V models.

FORM ONDULATO

MOD.	L cm	32	38	44	50	56	62	68	EN 442 Watt Δt 50 K	
H cm	(n° tubes)	(16t)	(19t)	(22t)	(25t)	(28t)	(31t)	(34t)	(37t)	(40t)
FO 180	€	668,50 742w	702,90 882w	746,90 1021w	786,00 1160w	860,60 1299w	924,30 1438w	998,50 1578w	1063,70 1717w	1138,00 1856w
FO 190	€	699,30 778w	734,50 923w	768,80 1069w	821,30 1215w	886,90 1361w	965,70 1507w	1033,00 1652w	1109,50 1798w	1179,00 1944w
FO 200	€	727,80 816w	755,40 969w	801,20 1122w	845,00 1275w	925,10 1427w	995,90 1580w	1076,10 1733w	1145,60 1886w	1218,00 2039w
FO 210	€	745,90 852w	786,00 1012w	823,00 1171w	878,50 1331w	951,90 1491w	1035,90 1650w	1107,50 1810w	1181,00 1970w	1255,40 2130w
FO 220	€	764,20 887w	804,80 1053w	854,80 1219w	901,40 1386w	987,30 1552w	1063,70 1718w	1138,00 1884w	1216,40 2051w	1292,60 2217w

On request, made-to-measure Heights from 140 to 300 cm.

Δt different from 50 K: technical data Brem

FORM ONDULATO CROM


MOD.	L cm	32	38	44	50	56	62	68	EN 442 Watt Δt 50 K	
H cm	(n° tubes)	(16t)	(19t)	(22t)	(25t)	(28t)	(31t)	(34t)	(37t)	(40t)
FOR 180	€	1739,90 594w	1862,70 706w	1996,40 817w	2137,40 928w	2378,00 1039w	2609,80 1150w	2850,50 1263w		
FOR 190	€	1822,50 622w	1950,00 738w	2075,80 855w	2238,00 972w	2475,30 1089w	2730,80 1206w	2973,30 1322w		
FOR 200	€	1902,00 653w	2035,50 775w	2165,20 898w	2324,20 1020w	2586,40 1142w	2839,80 1264w	3101,70 1386w		

On request, made-to-measure Heights from 140 to 200 cm

FORM ONDULATO (wavy) is made-to-measure on the basis of the following specifications:

- ends of tubes with a minimum of 15 cm straight pipe
- radius of curvature greater than 15 cm
- tolerance ± 3 mm
- depth ≤ 36 cm

Attach drawing with measurements for estimate.



STANDARD PRODUCTION

White "sablé" paintwork-white M4F brackets
Chrome-plated finish - chrome-plated brackets
Tolerance ± 3 mm -Max. working pressure 8Bar

PRODUCTION ON REQUEST

Brem color chart painting with chrome-plated brackets
+15/25%
p.289
Supports and fixings

STANDARD FITTING

EG $\varnothing 1/2"$
Air vent $\varnothing 1/8"$
 $\blacktriangle \nabla$ (t.c.) = L - 4 cm

