

Hudevad P5 Swing

The Hudevad P5 Swing is the vertical sister to P5 Easy Clean. The Hudevad P5 Swing has look and feel of the Hudevad P5 radiator, but with a few different touches. The P5 Swing can be opened like a door to provide access to comfortable and thorough cleaning of the rear side. Hudevad P5 Swing has a smooth, rebated, water-filled front plate. It has an easy-to-clean flat front, profiled edges and closed sides. Durable, turnable brackets for access to back. Closing function with magnet.

Material	2.00 mm steel plate according to EN 10051
Test pressure	10 bar
Max. operating pressure	7.7 bar in accordance with EN 442
Max. operating temperature	95°C
Surface treatment	Pretreatment: Degreasing, washing, and passivation Priming: Primed with water based paint in pale grey Surface treatment in accordance with DIN 55900 and EN 442
Length	P5V and P5V-D: 300, 400, 500, 600, 700 and 1000 mm Types 43C/108C (P5V/P5V-D) only apply to 1000 mm length - see page 3
Height	P5V and P5V-D: 800-2500 mm, in increments of 33.33 mm Heights between 2500 and 4000 mm are available
Depth	P5V: 40 mm, P5V 43C: 43 mm P5VD: 105 mm, P5VD 108C: 108 mm
Tappings	1/2" standard, adapter for 3/4"
Installation	Wall mounted Brackets are included Air vents and plugs are included
Optional extras	Towel rails/towel pegs Adjustable brackets
Colour	Powder-coated white RAL 9010, gloss 70 Option: Painted in other standard RAL and BS colours