





TUDOR

Quality fit for a King. This towel rail looks simple, but it has been carefully designed for maximum heating performance and capacity. Just don't lose your head deciding where to put it.

T Model shown on opposite page: TDR412-P (polished)

TUDOR

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Towel Gaps	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
									Choice of Elements (Watts)		
TDR408	800	420	100	E/H/D	2	3	642	188	400		S,P
TDR412	1200	420	100	E/H/D	3	4	857	251	600		S,P
TDR508	800	520	100	E/H/D	2	3	693	203	400		S,P
TDR512	1200	520	100	E/H/D	3	4	926	271	400	600	S,P
TDR608	800	620	100	E/H/D	2	3	748	219	400	600	S,P
TDR612	1200	620	100	E/H/D	3	4	1001	293	400	600	S,P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

