


Fiona One



Fiona One 1620↑ × 480⇔ E1
colour: Sparkling Gravel

ONE heating element




TERMA
SINCE 1990


Fiona One



Standard connections:




Electric radiators:



Specifications:



Working pressure: 1000 kPa Maximum operating temperature: 82°C

Optional connections:





Electrical specification:

| | |
|---------------------------------|---------------|
| Power supply: | 230 V / 50 Hz |
| Device protection class: | Class I |
| Ingress protection [IP]: | IPx5 |

| A ↓ [mm] | B ↔ [mm] | 75/65/20°C [W] | 55/45/20°C [W] |  [W] | D [mm] | E [mm] | F [mm] | H [dm³] |  [kg] | Product Code <small>configuration code p. 7</small> |
|--------------|-------------|-------------------|-------------------|---|-----------|-----------|-----------|------------|--|--|
| Paint | | | | | | | | | | |
| 900 | 400 | 305 | 162 | 400 | 370 | 760 | 70 | 2,87 | 6,00 | WZFIE090040 |
| 900 | 430 | 342 | 182 | 400 | 400 | 760 | 70 | 3,01 | 6,32 | WZFIE090043 |
| 900 | 480 | 375 | 200 | 400 | 450 | 760 | 70 | 3,25 | 6,85 | WZFIE090048 |
| 900 | 500 | 382 | 203 | 400 | 470 | 760 | 70 | 3,35 | 7,07 | WZFIE090050 |
| 900 | 530 | 407 | 217 | 400 | 500 | 760 | 70 | 3,49 | 7,39 | WZFIE090053 |
| 900 | 580 | 438 | 234 | 400 | 550 | 760 | 70 | 3,73 | 7,92 | WZFIE090058 |
| 900 | 600 | 458 | 244 | 400 | 570 | 760 | 70 | 3,82 | 8,14 | WZFIE090060 |
| 900 | 630 | 469 | 251 | 400 | 600 | 760 | 70 | 3,97 | 8,46 | WZFIE090063 |
| 900 | 680 | 500 | 267 | 400 | 650 | 760 | 70 | 4,21 | 8,99 | WZFIE090068 |
| 1140 | 400 | 385 | 204 | 400 | 370 | 1000 | 70 | 3,62 | 7,52 | WZFIE114040 |
| 1140 | 430 | 430 | 228 | 400 | 400 | 1000 | 70 | 3,80 | 7,92 | WZFIE114043 |
| 1140 | 480 | 471 | 250 | 400 | 450 | 1000 | 70 | 4,10 | 8,59 | WZFIE114048 |
| 1140 | 500 | 481 | 256 | 400 | 470 | 1000 | 70 | 4,22 | 8,86 | WZFIE114050 |
| 1140 | 530 | 511 | 272 | 600 | 500 | 1000 | 70 | 4,40 | 9,26 | WZFIE114053 |
| 1140 | 580 | 550 | 293 | 600 | 550 | 1000 | 70 | 4,70 | 9,93 | WZFIE114058 |
| 1140 | 600 | 577 | 307 | 600 | 570 | 1000 | 70 | 4,82 | 10,19 | WZFIE114060 |
| 1140 | 630 | 589 | 314 | 600 | 600 | 1000 | 70 | 5,00 | 10,59 | WZFIE114063 |
| 1140 | 680 | 628 | 335 | 600 | 650 | 1000 | 70 | 5,30 | 11,26 | WZFIE114068 |
| 1380 | 400 | 464 | 246 | 600 | 370 | 1240 | 70 | 4,38 | 9,04 | WZFIE138040 |
| 1380 | 430 | 518 | 275 | 600 | 400 | 1240 | 70 | 4,59 | 9,53 | WZFIE138043 |
| 1380 | 480 | 568 | 301 | 600 | 450 | 1240 | 70 | 4,95 | 10,33 | WZFIE138048 |
| 1380 | 500 | 580 | 308 | 600 | 470 | 1240 | 70 | 5,09 | 10,65 | WZFIE138050 |
| 1380 | 530 | 616 | 327 | 600 | 500 | 1240 | 70 | 5,31 | 11,13 | WZFIE138053 |
| 1380 | 580 | 664 | 352 | 600 | 550 | 1240 | 70 | 5,67 | 11,93 | WZFIE138058 |
| 1380 | 600 | 696 | 370 | 600 | 570 | 1240 | 70 | 5,81 | 12,25 | WZFIE138060 |
| 1380 | 630 | 711 | 378 | 800 | 600 | 1240 | 70 | 6,03 | 12,73 | WZFIE138063 |
| 1380 | 680 | 757 | 402 | 800 | 650 | 1240 | 70 | 6,38 | 13,53 | WZFIE138068 |
| 1620 | 400 | 543 | 287 | 800 | 370 | 1480 | 70 | 5,13 | 10,57 | WZFIE162040 |
| 1620 | 430 | 608 | 322 | 600 | 400 | 1480 | 70 | 5,38 | 11,13 | WZFIE162043 |
| 1620 | 480 | 666 | 353 | 600 | 450 | 1480 | 70 | 5,80 | 12,06 | WZFIE162048 |




Fiona One



| A ↓ [mm] | B ↔ [mm] | 75/65/20°C [W] | 55/45/20°C [W] |  [W] | D [mm] | E [mm] | F [mm] | H [dm³] |  [kg] | Product Code <small>configuration code p. 7</small> |
|----------------|-------------|-------------------|-------------------|--|-----------|-----------|-----------|------------|---|--|
| 1620 | 500 | 679 | 359 | 600 | 470 | 1480 | 70 | 5,97 | 12,44 | WZFIE162050 |
| 1620 | 530 | 723 | 383 | 800 | 500 | 1480 | 70 | 6,22 | 13,00 | WZFIE162053 |
| 1620 | 580 | 779 | 413 | 800 | 550 | 1480 | 70 | 6,64 | 13,93 | WZFIE162058 |
| 1620 | 600 | 815 | 432 | 800 | 570 | 1480 | 70 | 6,81 | 14,31 | WZFIE162060 |
| 1620 | 630 | 834 | 442 | 800 | 600 | 1480 | 70 | 7,06 | 14,87 | WZFIE162063 |
| 1620 | 680 | 889 | 471 | 800 | 650 | 1480 | 70 | 7,47 | 15,80 | WZFIE162068 |
| 1860 | 400 | 623 | 329 | 800 | 370 | 1720 | 70 | 5,89 | 12,09 | WZFIE186040 |
| 1860 | 430 | 700 | 370 | 800 | 400 | 1720 | 70 | 6,18 | 12,73 | WZFIE186043 |
| 1860 | 480 | 767 | 405 | 800 | 450 | 1720 | 70 | 6,65 | 13,80 | WZFIE186048 |
| 1860 | 500 | 778 | 411 | 800 | 470 | 1720 | 70 | 6,84 | 14,23 | WZFIE186050 |
| 1860 | 530 | 832 | 440 | 800 | 500 | 1720 | 70 | 7,13 | 14,87 | WZFIE186053 |
| 1860 | 580 | 897 | 474 | 1000 | 550 | 1720 | 70 | 7,61 | 15,94 | WZFIE186058 |
| 1860 | 600 | 934 | 493 | 1000 | 570 | 1720 | 70 | 7,80 | 16,37 | WZFIE186060 |
| 1860 | 630 | 960 | 507 | 1000 | 600 | 1720 | 70 | 8,09 | 17,01 | WZFIE186063 |
| 1860 | 680 | 1023 | 541 | 1000 | 650 | 1720 | 70 | 8,56 | 18,08 | WZFIE186068 |
| Plating | | | | | | | | | | |
| 900 | 400 | 214 | 113 | 200 | 370 | 760 | 70 | 2,87 | 5,77 | WZFIE090040 |
| 900 | 430 | 240 | 127 | 300 | 400 | 760 | 70 | 3,01 | 6,08 | WZFIE090043 |
| 900 | 480 | 262 | 140 | 300 | 450 | 760 | 70 | 3,25 | 6,59 | WZFIE090048 |
| 900 | 500 | 267 | 142 | 300 | 470 | 760 | 70 | 3,35 | 6,79 | WZFIE090050 |
| 900 | 530 | 285 | 152 | 300 | 500 | 760 | 70 | 3,49 | 7,10 | WZFIE090053 |
| 900 | 580 | 307 | 164 | 300 | 550 | 760 | 70 | 3,73 | 7,61 | WZFIE090058 |
| 900 | 600 | 321 | 171 | 300 | 570 | 760 | 70 | 3,82 | 7,82 | WZFIE090060 |
| 900 | 630 | 329 | 176 | 300 | 600 | 760 | 70 | 3,97 | 8,13 | WZFIE090063 |
| 900 | 680 | 350 | 187 | 300 | 650 | 760 | 70 | 4,21 | 8,64 | WZFIE090068 |
| 1140 | 400 | 270 | 143 | 300 | 370 | 1000 | 70 | 3,62 | 7,23 | WZFIE114040 |
| 1140 | 430 | 301 | 160 | 300 | 400 | 1000 | 70 | 3,80 | 7,62 | WZFIE114043 |
| 1140 | 480 | 329 | 175 | 300 | 450 | 1000 | 70 | 4,10 | 8,26 | WZFIE114048 |
| 1140 | 500 | 337 | 179 | 400 | 470 | 1000 | 70 | 4,22 | 8,52 | WZFIE114050 |
| 1140 | 530 | 358 | 190 | 400 | 500 | 1000 | 70 | 4,40 | 8,90 | WZFIE114053 |
| 1140 | 580 | 385 | 205 | 400 | 550 | 1000 | 70 | 4,70 | 9,54 | WZFIE114058 |
| 1140 | 600 | 404 | 215 | 400 | 570 | 1000 | 70 | 4,82 | 9,80 | WZFIE114060 |
| 1140 | 630 | 413 | 220 | 400 | 600 | 1000 | 70 | 5,00 | 10,18 | WZFIE114063 |
| 1140 | 680 | 440 | 235 | 400 | 650 | 1000 | 70 | 5,30 | 10,82 | WZFIE114068 |
| 1380 | 400 | 325 | 172 | 400 | 370 | 1240 | 70 | 4,38 | 8,70 | WZFIE138040 |
| 1380 | 430 | 363 | 193 | 400 | 400 | 1240 | 70 | 4,59 | 9,16 | WZFIE138043 |
| 1380 | 480 | 397 | 211 | 400 | 450 | 1240 | 70 | 4,95 | 9,93 | WZFIE138048 |
| 1380 | 500 | 406 | 216 | 400 | 470 | 1240 | 70 | 5,09 | 10,24 | WZFIE138050 |
| 1380 | 530 | 431 | 229 | 400 | 500 | 1240 | 70 | 5,31 | 10,70 | WZFIE138053 |
| 1380 | 580 | 465 | 246 | 400 | 550 | 1240 | 70 | 5,67 | 11,47 | WZFIE138058 |
| 1380 | 600 | 487 | 259 | 400 | 570 | 1240 | 70 | 5,81 | 11,77 | WZFIE138060 |
| 1380 | 630 | 498 | 265 | 600 | 600 | 1240 | 70 | 6,03 | 12,23 | WZFIE138063 |
| 1380 | 680 | 530 | 281 | 600 | 650 | 1240 | 70 | 6,38 | 13,00 | WZFIE138068 |

Fiona One








| A ↓ [mm] | B ↔ [mm] | 75/65 20°C [W] | 55/45 20°C [W] |  [W] | D [mm] | E [mm] | F [mm] |  [dm³] |  [kg] | Product Code <small>configuration code p. 8</small> |
|----------------|-------------|-------------------|-------------------|--|-----------|-----------|-----------|--|---|--|
| Plating | | | | | | | | | | |
| 1620 | 400 | 380 | 201 | 400 | 370 | 1480 | 70 | 5,13 | 10,16 | WZFIE162040 |
| 1620 | 430 | 426 | 225 | 400 | 400 | 1480 | 70 | 5,38 | 10,70 | WZFIE162043 |
| 1620 | 480 | 466 | 247 | 400 | 450 | 1480 | 70 | 5,80 | 11,60 | WZFIE162048 |
| 1620 | 500 | 475 | 251 | 600 | 470 | 1480 | 70 | 5,97 | 11,96 | WZFIE162050 |
| 1620 | 530 | 506 | 268 | 600 | 500 | 1480 | 70 | 6,22 | 12,49 | WZFIE162053 |
| 1620 | 580 | 545 | 289 | 600 | 550 | 1480 | 70 | 6,64 | 13,39 | WZFIE162058 |
| 1620 | 600 | 571 | 302 | 600 | 570 | 1480 | 70 | 6,81 | 13,75 | WZFIE162060 |
| 1620 | 630 | 584 | 309 | 600 | 600 | 1480 | 70 | 7,06 | 14,29 | WZFIE162063 |
| 1620 | 680 | 622 | 330 | 600 | 650 | 1480 | 70 | 7,47 | 15,18 | WZFIE162068 |

Fiona One




Available sizes:



Fiona One





Technical drawing:



A – Height B – Width C1-C5 – Distance between pipe centres D – Horizontal distance between mounting bracket centres
E – Vertical distance between mounting brackets F – Distance between a mounting bracket and the bottom of the radiator

Collector:

Pipe:





In the table with technical data, the last column lists product codes. When placing an order, please remember to quote the product code followed by the configuration code as shown in the diagram below:

The construction of a configuration code of a water radiator with a built-in One heating element:

WZFI090040

PRODUCT CODE
(located in the table for the product)

K916S1

CONIGURATION CODE
(supplemented by hand)

Cable Type

W – straight cable with plug
P – straight cable without plug
U – spiral cable with plug

Example Configuration

K 916 S1 P

Package code Plate color code Connection code Cable Type code
K - carton box

The Construction of the product and configuration code for a radiator with the built-in heating element ONE:

WWFI043043

PRODUCT CODE
(located in the table for the product)

K916E1

CONIGURATION CODE
(supplemented by hand)

Cable Type

W – straight cable with plug
P – straight cable without plug
U – spiral cable with plug

Example Configuration

K 916 E1 P

Package code Plate color code Connection code Cable Type code
K - carton box

Epoxy primer

E – Code of epoxy primer is an extra processes.

WZFI090040 K916S1 **E** — Extra processes or additions code

Fiona One



Legend




Radiator suitable in "sinter" version.



Radiator suitable for dual fuel connection. Electric heating element can be installed.



Radiator available in electric only version. It comes prefilled with a 'heating medium' and equipped with a heating element. All tested and ready to use.



Connection types dedicated for this radiator. The icon shows the flow and return connections for the radiator as well as the thermostatic valve and heating element position if applicable.



Suggested heating element power output for electric and dual fuel versions.



Weight.



Capacity.



Available in chrome finish.



No additional payment for a color.